

RH1- RH2



ReddiLight

FEATURES

PRE WIRED

LOW POWER CONSUMPTION

DUSK TO DAWN OPERATION

240V (24V AVAILABLE)

DIMENSIONS

L550mmXW85mmXH280mm

10 YEAR WARRANTY

WEIGHT 4KG

UMSUG CODE – 40-0003-0007-100

LONG LIFE LED

IP66 RATED

LIGHTS SIGN 600mm OR 750mm
ACROSS, 1500mm DOWN

FITS 76mm POST STANDARD BUT
BRACKETS AVAILABLE FOR OTHER SIZES

AVAILABLE IN BLACK, GREY OR SILVER

PHONE:

01527 502670

E. MAIL

reddilightltd@msn.com



TECHNICAL DATA

CABLE	3138Y MAINS	BSEN50525-2-11
PHOTOCELL	35/28 LUX 12 YEAR WARRANTY	EN55015EN61000 EN61347 EN61547
ENTERPRISE	LM6 ALUMINIUM CAST	
LED	1 X 3W 50,000 HR	EN55015, EN61547 EN61000 EN62031
DRIVER	12W 24V 0.5A CONSTANT VOLTAGE	EN55015 EN61000 EN61547
BODY	IMPACT GRADE ABS	ASTM D648, I IEC60112
ILLUMINANCE - E2 UE2		
OPERATING TEMP RANGE -15° to +50°		

