

RS1- 65W



ReddiLight

FEATURES

PRE WIRED

LOW POWER CONSUMPTION

DUSK TO DAWN OPERATION

ZERO OPERATING CARBON EMISSIONS

INCORPORATES ENTERPRISE SIGN LIGHT

DIMENSIONS 830 mm ROUND

4 YEAR WARRANTY

WEIGHT 26KG

65W PANEL INCREASES CHARGE RATE

LONG LIFE LED

CHARGES IN ALL WEATHER
CONDITIONS

FITS 76mm POST STANDARD BUT
BRACKETS AVAILABLE FOR OTHER SIZES

ILLUMINATES UP TO 900mm SIGN

AVAILABLE IN BLACK, GREY OR SILVER

PHONE:

01527 502670

E. MAIL

reddilightltd@msn.com



TECHNICAL DATA

BATTERY	12V 50AH	EU2015/830 EU1272/2008
PANEL	65W TOUGHNED GLASS	BSEN12150
CONTROLLER	12/24V DC - RANGE 8-32V	IEC62852 EN61000-6-3-2007
ENTERPRISE	LM6 ALUMINIUM CAST	BSEN485-2.2013
LED	1 X 0.3W 50,000 HR	EN55015, EN61547 EN61000 EN62031
PHOTOCELL	12V 70LUX	EN55015 EN61000 EN61347
BODY	IMPACT GRADE ABS	ASTM D648, I IEC60112
ILLUMINANCE - E2 UE2		
OPERATING TEMP RANGE -15° to +50°		